

GFCI In-Line Cord Sets

Excellent for industrial plant maintenance, equipment service and construction site applications. Provides compliance with National Electric Code (NEC 2008) Article 590.6 for "Temporary Installations". Applications include:

- ▶ High Pressure Sprayer Washers
- ▶ Drain Snakes
- ▶ Construction Sites
- ▶ Construction Site Power Tools
- ▶ Pumps
- ▶ Industrial Appliances

Rainproof rated, UL listed for outdoor use. Standard Lengths: 2', 6', 25', 50' Custom cable gauges, lengths and terminations available by special order. To prevent unmonitored equipment startup, manual reset is required after GFCI trip and power outage.

FEATURES

- | | |
|--|--------------------------------|
| 25080-011(2') ☹ | 25090-001(2') ☹ |
| 25080-016(6') | 25090-006(6') |
| 25080-025(25') | 25090-025(25') |
| ▶ Volts /Amps: 120V/20A | ▶ Volts /Amps: 240V/15A |
| ▶ Cord Gauge: 12/3 AWG. | ▶ Cord Gauge: 14/3 AWG. |
| ▶ NEMA 5 - 20 P & R (yellow) | ▶ NEMA 6 - 15 P & R (yellow) |
| ▶ Trip Level: 4 - 6 mA | ▶ Trip Level: 4 - 6 mA |
| 26020-002(2') ☹ | 26000-011(2') ☹ |
| 26020-007(6') | 26000-016(6') |
| 26020-124(25') | 26000-125(25') |
| 26020-050(50') | ▶ Volts /Amps: 240V/20A |
| 26020-099(100') | ▶ Cord Gauge: 12/3 AWG. |
| ▶ Volts /Amps: 120V/15A | ▶ NEMA 6 - 20 P & R (black) |
| ▶ Cord Gauge: 14/3 or 12/3 AWG. | ▶ Trip Level: 4 - 6 mA |
| ▶ NEMA 5 - 15 P & R (black) | |
| ▶ Trip Level: 4 - 6 mA | |
| ▶ Also available in 100' length | |
| ▶ Also available with lighted receptacle | |



TECHNICAL DATA

Grounded Neutral	4 Ohms typical
Trip response time for ground fault and grounded neutral trip	less than 25mS
Voltage surge withstand	3kv ringwave test and 4kv/2kA surge immunity test
Radio frequency noise susceptibility	operates within normal limits with 0.5 volts injected on power line 150kHz-230mHz
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-35°C to 66°C
Effect of 10 Amp turn DC Shock on ground fault trip	5% maximum trip level variation
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator

