

# HD-PRO™ 10.30.50

# HD-PRO™ 6.10.30



## High Power Equipment Ground Fault Protective Devices (EGFPD) and GFCI/ELCI Adjustables

Configured for both in-line and bulk head mount. Engineered to trip within 25 milliseconds. Protects:

- ▶ Motors
- ▶ Pumping Systems
- ▶ Pressure Washers
- ▶ Manufacturing Equipment
- ▶ Welders
- ▶ Hoists

To prevent equipment startup after EGFPD or GFCI/ELCI trips, manual reset required. Will reset on power restoration following disruption of primary power. Key enables trip level selection and locks at a trip level with key removal.

### FEATURES

#### 44110 EGFPD\*

- ▶ Volts/Amps: 208-240V/30A
- ▶ Trip Level: 10, 30 & 50 mA
- ▶ Three Phase

#### 44140 EGFPD\*

- ▶ Volts/Amps: 208-240V/60A
- ▶ Trip Level: 10, 30 & 50 mA
- ▶ Three Phase

#### 44120 EGFPD\*

- ▶ Volts/Amps: 480V/30A
- ▶ Trip Level: 10, 30 & 50 mA
- ▶ Three Phase

#### 44130 EGFPD\*

- ▶ Volts/Amps: 480V/60A
- ▶ Trip Level: 10, 30 & 50 mA
- ▶ Three Phase



#### 44610 GFCI/ELCI

- ▶ Volts/Amps: 208-240V/30A
- ▶ Trip Level: 6, 10 & 30 mA
- ▶ Three Phase

#### 44640 GFCI/ELCI

- ▶ Volts/Amps: 208-240V/60A
- ▶ Trip Level: 6, 10 & 30 mA
- ▶ Three Phase

#### 44620 GFCI/ELCI

- ▶ Volts/Amps: 480V/30A
- ▶ Trip Level: 6, 10 & 30 mA
- ▶ Three Phase

#### 44630 GFCI/ELCI

- ▶ Volts/Amps: 480V/60A
- ▶ Trip Level: 6, 10 & 30 mA
- ▶ Three Phase



10.30.50 version pictured

### TECHNICAL DATA

Response time for ground fault	25mS - typical
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-20° C to +40° C
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator
Drop out voltage	60% rated voltage - typical
Reset type	auto
Connection type	user attachable
Enclosure	NEMA 4 16 guage steel

