

# Heavy Duty - High Power ELCIs

Configured for both in-line and bulk head mount. Engineered to trip within 25 milliseconds. Protects:

- ▶ Motors
- ▶ Pumping Systems
- ▶ Pressure Washers
- ▶ Manufacturing Equipment
- ▶ Welders
- ▶ Hoists

Has 2' of cable on both line and load side. To prevent equipment startup after ELCI trips, manual reset required. Will reset on power restoration following disruption of primary power.

## FEATURES

### 24520-001

- ▶ Volts/Amps: **120V/60A**
- ▶ Cord Gauge: 4/3 AWG.
- ▶ Trip Level: 10 mA
- ▶ Single Phase

### 25560-001

- ▶ Volts/Amps: **380V/60A**
- ▶ Cord Gauge: 4/4 AWG.
- ▶ Trip Level: 30 mA
- ▶ Three Phase

### 24530-001

- ▶ Volts/Amps: **240V/60A**
- ▶ Cord Gauge: 4/4 AWG.
- ▶ Trip Level: 10 mA
- ▶ Three Phase

## TECHNICAL DATA

Response time for ground fault	25mS - typical
Frequency	50 / 60 Hz
Endurance	3,000 operations minimum
Overload Current	six times rated current
Operating temperature range	-20° C to +40° C
Insulation voltage	1500 VRMS - 1 Min.
Power On indication	lighted indicator
Drop out voltage	60% rated voltage - typical
Reset type	auto
Connection type	flying leads
Enclosure	NEMA 4 polymer

